

QUALITY

Nr. 14 NR
Natural Rubber



Technical datasheet

| | |
|--------------------|----------------------------------|
| Quality | <i>Nr. 14 NR- Natural Rubber</i> |
| Top Surface | <i>sand surface</i> |
| Color | <i>beige</i> |

| | |
|------------------------------|--|
| Available widths (mm) | <i>50, 70, 100, 500</i> |
| Others | <i>on request available</i> |
| Available lengths (m) | <i>Rolls of app 55mtr. (-0 / +5mtr.)</i> |
| Others | <i>on request available</i> |
| Thickness | <i>2,3mm (+/- 0,10)</i> |
| Shore hardness A | <i>45 (+/- 3)</i> |
| Abrasion | <i>< 300 mg/cm²</i> |
| Weight p/unit | <i>2100 g/m² (+/- 3,5%)</i> |
| Temperature Range | <i>max. 100°C</i> |
| Plies | <i>1 ply cotton polyester</i> |

| | |
|----------------------------|----------------------------|
| Chemical resistance | |
| Oil, grease | <i>moderate resistance</i> |
| Acids, salt, bases | <i>moderate resistance</i> |

NOTE

The above-mentioned data is tested on a individual basis. All test data are average values and should be considered as guidelines; therefore Kolthoff – LKB GmbH cannot be held accountable for the above-mentioned figures.
