


QUALITY

Nr. 27 - Carboxylated  
Synthetic (XNBR) Rubber  
*Carboxylated Nitrile Butadiene rubber*



## Technical datasheet

---

<b>Quality</b>	<i>Nr. 27 synthetic Rubber</i>
<b>Top Surface</b>	<i>supergrip surface</i>
<b>Color</b>	<i>patrol</i>

---

<b>Available widths (mm)</b>	<i>50, 70, 100, 500</i>
<b>Others</b>	<i>on request available</i>
<b>Available lengths (m)</b>	<i>Rolls of app 50mtr. (-0 / +5mtr.)</i>
<b>Others</b>	<i>on request available</i>
<b>Thickness</b>	<i>4,5mm (+/- 0,10)</i>
<b>Shore hardness A</b>	<i>60 (+/- 3)</i>
<b>Abrasion</b>	<i>&lt; 200 mg/cm<sup>2</sup></i>
<b>Weight p/unit</b>	<i>2400 g/m<sup>2</sup> (+/- 3,5%)</i>
<b>Temperature Range</b>	<i>max. 70°C</i>
<b>Plies</b>	<i>1 ply cotton polyester</i>

---

<b>Chemical resistance</b>	
<b>Oil, grease</b>	<i>excellent resistance</i>
<b>Acids, salt, bases</b>	<i>excellent resistance</i>

---

NOTE

*The above-mentioned data is tested on a individual basis. All test data are average values and should be considered as guidelines; therefore Kolthoff – LKB GmbH cannot be held accountable for the above-mentioned figures.*

---